

TECHNICAL DATA SHEET

UNIQUE BF Q653

Product Information:

Revision index / date: A, January 2018

UNIQUE BF Q653

Full Synthetic

Description:

High-performance synthetic fluid suited to braking systems that use a synthetic fluid. This fluid can also be used in clutch assistance systems that use a synthetic fluid.

Precautions for use:

- Always keep the brake fluid sealed in its original packaging
- Any contamination with dust, water, petroleum products or other materials can cause incidents during brake operation.
- Do not top up the container
- Do not mix the brake fluid with a mineral fluid (L.H.M.)
- Do not reuse the packaging
- Brake fluids are corrosive to paintwork. Should it drip on the bodywork, rinse with water and wipe clean.

Product features:

- Miscible with other brake fluids of the same grade.

Application:

Braking systems

Specifications:

SAE J 1703 / J1704, FMVSS 116 DOT3, DOT4 & DOT 5.1, ISO 4925, VV-B-680B, JIS K 2233.

Complies with the manufacturers' requirements for vehicles equipped with the 'Electronic Stability Program' (ESP) system.

Packaging:

1 x 0.5 L

Typical data:

Characteristics	Method	Units	Typical	Mini
Kinematic viscosity @ -40°C	ASTM D 7279	cSt	770	-
Boiling point	DOT4	°C	272	260
Wet boiling point	DOT4	°C	186	180
Appearance / color	Visual	-	Limpid light yellow	
pH		pH	7,5	7,0

The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies.